

694	青銅バルブ(コアリング)	 株式会社 大和精工
改定2007.7	【新定価 2007年7月～】	

品 種	ゲート				スイングチェッキ		Y形ストレーナ		ハンマレスチェッキ		
外観形状									(衝撃吸取式)		
規 格	JV5	JV5	JV5	JV5	JV5	JV5	JV5	JV5	JV5		
圧 力	5K		10K		10K		10K		10K		
管 接 続	ねじ込み										
本体材質	CAC406										
用 途	塩ビ・ポリ粉兼用	耐熱塩ビ用	塩ビ・ポリ粉兼用	耐熱塩ビ用	塩ビ・ポリ粉兼用	耐熱塩ビ用	塩ビ・ポリ粉兼用	耐熱塩ビ用	塩ビ・ポリ粉兼用		
呼径	製品記号	5G-CN	5G-HN	10G-CN	10G-HN	10C-CN	10C-HN	10Y-CN	10Y-HN	HC-CN	
	1/2 ^B	15 ^A	3,930	3,930	5,430	5,430	4,660	4,660	3,670	3,670	
	3/4	20	5,230	5,230	7,680	7,680	5,860	5,860	4,600	4,600	5,200
	1	25	7,110	7,110	10,700	10,700	8,560	8,560	7,460	7,460	7,910
	1 1/4	32	12,000	12,000	16,700	16,700	15,000	15,000	10,900	10,900	
	1 1/2	40	15,900	15,900	22,600	22,600	18,100	18,100	13,500	13,500	
	2	50	24,200	24,200	32,600	32,600	29,200	29,200	22,600	22,600	
備 考	<p>(JV5)塩ビ・ポリ粉兼用コアリングバルブ、及び(JV5)耐熱塩ビ用コアリングバルブは国土交通省「機械設備工事編」に適合します。</p> <p>給水器具認証登録品の検査証印付の製品をお求めの場合は実費が加算されます。</p>										

693	青銅バルブ(鉛レス)	 株式会社 大和精工
改定2007.7	【新定価 2007年7月～】	

品 種	ゲート		ゲート		Y形ストレーナ	ストップ		スイングチェッキ			
外観形状											
規 格	JIS B 2011				大和型	JIS 適合品	JIS B 2011		JIS 適合品		
圧 力	5K	10K	5K	10K	10K	5K	10K	10K	10K		
管 接 続	ねじ込み		ソルダー			ねじ込み		ソルダー			
本体材質	CAC406										
ス テ ム	NBY		CAC406C			NBY		C3604	CAC406C		
呼径	製品記号	B5GN	B10GN	B5DGN	B10DGN	B10YN	B5SN	B10SN	B10CN	B10DCN	
	1/4 ^B	8 ^A						3,840			
	3/8	10						4,100			
	1/2	15	3,600	5,030	4,200	5,900	3,320	3,840	4,600	4,320	
	3/4	20	4,800	7,090	5,580	8,290	4,320	4,940	6,140	5,450	5,470
	1	25	6,550	9,860	7,690	12,500	6,370	6,950	8,460	7,860	7,160
	1 1/4	32	11,000	15,100	12,800	19,500	9,210	13,000	16,100	13,700	11,100
	1 1/2	40	14,600	21,200	16,800	26,400	11,600	15,100	17,600	16,900	14,500
	2	50	21,500	30,100	26,300	38,100	19,500	24,700	28,400	27,200	22,100
	2 1/2	65	46,000	58,000		※ 70,700	47,700				※ 38,900
	3	80	68,000	92,700		※ 113,000					
	4	100									
備 考	<p>製品記号B10YN給水器具認証登録品の検査証印付の製品をお求めの場合は実費が加算されます。</p> <p>※印はJIS規格に準じて製作したものです。</p>										