

火無し継手の工事には施工講習の受講が必要です。

継手 K-HMJ



K-HMJ28



K-HMJ09



厚さ20mm保温材付

品番	接続銅管サイズ (mm)	本体二面幅 (mm)	ナット二面幅 (mm)	価格
K-HMJ06	6.35	13	16	1,350
K-HMJ09	9.52	17	22	1,400
K-HMJ12	12.70	21	24	1,600
K-HMJ15	15.88	24	27	1,800
K-HMJ19	19.05	27	32	2,250
K-HMJ22	22.22	30	34	2,650
K-HMJ25	25.40	36	40	3,300
K-HMJ28	28.58	41	44	4,100
K-HMJ31	31.75	46	48	5,700
K-HMJ38	38.10	50	55	7,900

(単価：円/個)

異径継手 K-HMJR



K-HMJR2825



K-HMJR0906



厚さ20mm保温材付

品番	接続銅管サイズ (mm)	本体二面幅 (mm)	ナット二面幅 (mm)	価格
K-HMJR0906	9.52 × 6.35	17	22 × 16	2,400
K-HMJR1206	12.70 × 6.35	21	24 × 16	2,500
K-HMJR1209	12.70 × 9.52	21	24 × 22	2,500
K-HMJR1509	15.88 × 9.52	24	27 × 22	2,600
K-HMJR1512	15.88 × 12.70	24	27 × 24	2,600
K-HMJR1909	19.05 × 9.52	27	32 × 22	2,900
K-HMJR1912	19.05 × 12.70	27	32 × 24	2,900
K-HMJR1915	19.05 × 15.88	27	32 × 27	2,900
K-HMJR2212	22.22 × 12.70	30	34 × 24	3,450
K-HMJR2215	22.22 × 15.88	30	34 × 27	3,450
K-HMJR2219	22.22 × 19.05	30	34 × 32	3,450
K-HMJR2515	25.40 × 15.88	36	40 × 27	4,400
K-HMJR2519	25.40 × 19.05	36	40 × 32	4,400
K-HMJR2522	25.40 × 22.22	36	40 × 34	4,400
K-HMJR2822	28.58 × 22.22	41	44 × 34	5,200
K-HMJR2825	28.58 × 25.40	41	44 × 40	5,200
K-HMJR3122	31.75 × 22.22	46	48 × 34	8,300
K-HMJR3125	31.75 × 25.40	46	48 × 40	8,300
K-HMJR3128	31.75 × 28.58	46	48 × 44	8,300
K-HMJR3831	38.10 × 31.75	50	55 × 48	11,000

(単価：円/個)

L型継手 K-HMJE




保温材はついていません。

品番	接続銅管サイズ (mm)	本体二面幅 (mm)	ナット二面幅 (mm)	価格
K-HMJE22	22.22	30	34	8,500
K-HMJE25	25.40	36	40	9,500
K-HMJE28	28.58	41	44	11,500

(単価：円/個)

気密治具(気密テスト用) K-I



- φ6.4止めナット付き
- 配管端部止め用、ガス供給用兼用

品番	継手サイズ (mm)	価格
K-HMJK12	12.70	2,500
K-HMJK15	15.88	2,550
K-HMJK19	19.05	2,600
K-HMJK22	22.22	2,650
K-HMJK25	25.40	3,000
K-HMJK28	28.58	3,450
K-HMJK31	31.75	3,500
K-HMJK38	38.10	3,840

(単価：円/個)