

190	ガス用外面被覆継手 キーロンVI継手		株式会社 協成
改定2006.10	【新定価 2006年10月～】		

呼径	エルボ	チーズ	ソケット	プラグ	ストリート エルボ	呼径	連径90° エルボ	連径 チーズ	連径 ソケット
15	300	520	390	510	510	20 × 15	450	640	540
20	350	520	400	550	670	25 × 15	-	930	
25	570	900	580	840	920	25 × 20	800	930	690
32	1,030	1,340	830	1,090	1,510	32 × 20		1,430	
40	1,200	1,520	960	1,400	1,740	32 × 25	1,400	1,430	1,030
50	1,850	2,440	1,470	1,780	2,530	40 × 20		1,890	1,350
65	3,770	5,180	2,850			40 × 25		1,890	1,350
80	5,510	7,450	3,720			40 × 32	1,870	1,890	1,350
100	8,620	12,240	6,650			50 × 20		3,080	
						50 × 25		3,080	
						50 × 32		3,080	
						50 × 40	2,840	3,080	1,870
						65 × 50			
						80 × 50	8,580	9,130	4,730
						80 × 65			4,730
						100 × 50		15,440	
						100 × 65			7,960
						100 × 80	14,570	15,440	7,960

鉄管継手

191	ガス用 キ - ロンガスフレキ		株式会社 協成
改定2006.5	【新定価 2006年5月～】		

	長さ 呼び径	200	250	300	400	500	600	700	800	900	1000
		T1 (グレ - 色) 日本ガス機器 検査協会認証品	15A	2,850	3,070	3,150	3,410	4,480	4,840	5,920	6,260
	20A	3,550	3,780	4,190	4,660	5,230	5,650	6,770	7,160	7,890	8,290
T1-I (アイボリー - 色) 日本ガス機器 検査協会認証品	15A	2,850	3,070	3,150	3,410	4,480	4,840				
	20A	3,550	3,780	4,190	4,660	5,230	5,650				

140	ガス配管用防蝕継手 PLS継手	JFE継手株式会社
04.4		

品名 サイズ	エルボ (L)	45° エルボ (45° L)	ストリートエルボ (SL)	チーズ (T)	サービスチーズ (ST)	ソケット (S)	プラグ (P)
1/2	300		590	510		390	280
3/4	340	590	650	530	790	410	300
1	570	750	840	900	880	580	510
1 1/4	1,000		1,460	1,320	1,440	820	800
1 1/2	1,200		1,650	1,500	1,870	960	1,050
2	1,790		2,540	2,300	2,990	1,400	1,380
3	7,040			9,300		5,340	2,970
3/4 × 1/2	550			670		550	
1 × 1/2				860		630	
1 × 3/4	700			860		630	
1 1/4 × 1/2				1,420			
1 1/4 × 3/4				1,420		840	
1 1/4 × 1	1,340			1,420		840	
1 1/2 × 3/4				1,840			
1 1/2 × 1				1,840		1,160	
1 1/2 × 1 1/4				1,840		1,160	
2 × 1				2,990			
2 × 1 1/4				2,990		1,570	
2 × 1 1/2				2,990		1,570	
3 × 2				10,560			