



外観形状										
型式	600型	600型 蝶型ハンドル	1000型 ロングネック	800型	1000型 フルボア	1000型3分割形		800型4面 シートLポート	600型	
ボディシールシート	SCS14/SUS316		SCS13/SUS304	SCS14/SUS316		SCS14/SUS316		SCS14/SUS316	SCS13/SUS304	
管接続部	強化PTFE			PTFE			PTFE		ハイパタイトシート※	強化PTFE
管接続部	ねじ込					ねじ込	ソケットウェルド	ねじ込		
製品番号	UTKM	UTKMW	⑤UTHL	②UTHM	UTFM	U3TZM	SWU3TZM	UTH4LM	UTK	
呼径										
<sup>1</sup> / <sub>4</sub> B 8	2,760	2,760							2,220	
<sup>3</sup> / <sub>8</sub> 10	2,940	2,940							2,350	
<sup>1</sup> / <sub>2</sub> 15	3,650	3,650	6,590	5,270	8,260	9,180	10,700	28,700	2,910	
<sup>3</sup> / <sub>4</sub> 20	4,230	4,230	7,460	6,120	9,620	10,200	12,100	35,000	3,370	
1 25	5,340	5,340	10,300	8,540	13,600	15,200	18,100	44,400	4,240	
<sup>1</sup> / <sub>4</sub> 32	9,080		14,300	13,000	20,300	19,100	22,900	65,600	7,240	
<sup>1</sup> / <sub>2</sub> 40	11,900		18,200	16,800	26,400	24,500	29,400	73,300	9,370	
2 50	16,400		25,100	23,400	36,500	34,100	40,900	88,900	13,000	

⑤はSAS358準拠品です。

(単位：円)

Aシリーズ(適用規格：ANSI B16.34 管接続部：フランジJIS B2210/ANSI B16.5)									
外観形状	静電防止機構付 								
型式	フルボア					レデューストボア			
ボディシールシート	SCS13	SCS14	SCS13		SCS14	SCS16	SCS13	SCS14	
管接続部	PTFE			ハイパタイトシート※					
管接続部	ねじ込			フランジ					
製品番号	⑤10UT	10UTM	10UTBD	10UTB	10UTBDM	10UTBM	10UTBO	10UTR	10UTRM
呼径									
<sup>3</sup> / <sub>8</sub> B 10 <sup>A</sup>	8,760	12,400							
<sup>1</sup> / <sub>2</sub> 15	9,300	13,000	17,000	17,000	23,800	23,800	28,700		
<sup>3</sup> / <sub>4</sub> 20	11,400	16,000	19,500	19,500	27,500	27,500	33,200		
1 25	14,900	20,700	27,300	27,300	38,400	38,400	46,500		
<sup>1</sup> / <sub>4</sub> 32	21,200	29,800	34,700	34,700	48,700	48,700	59,100	◎	◎
<sup>1</sup> / <sub>2</sub> 40	28,500	39,700	37,200	37,200	52,100	52,100	63,300	◎	◎
2 50	36,300	50,600	47,300	47,300	66,300	66,300	80,500	45,900	64,400
<sup>2</sup> / <sub>2</sub> 65	58,200	81,700	69,300	69,300	97,100	97,100	119,000	67,400	94,400
3 80	77,000	108,000	82,300	82,300	116,000	116,000	140,000	79,500	112,000
4 100			121,000	121,000	169,000	169,000	207,000	115,000	165,000
5 125			282,000	282,000	394,000	394,000	478,000	205,000	288,000
6 150			349,000	349,000	489,000	489,000	593,000	304,000	426,000
8 200			580,000	580,000	812,000	812,000	986,000	436,000	612,000
10 250					◎	◎	◎	679,000	951,000

注)10UTBD、10UTBDMはAP16D面間です。◎印はSAS358準拠品です。

(単位：円)