

外観形状										
型式	600型		600型 蝶型ハンドル	800型	1000型 ロングネック	1000型 フルボア	1000型3分割形		800型4面 シートLポート	
ボディ/ボール	SCS13A/SUS304		SCS14A/SUS316		SCS13A/SUS304		SCS14A/SUS316			
シート	ガラスファイバー入PTFE				ハイパタイトPTFE					
管接続部	ねじ込						ねじ込	ソケットウェルド	ねじ込	
製品番号	UTK	UTKM	UTKMW	UTFZ	UTHL	UTFM	U3TZM	SWU3TZM	UTH4LM	
呼径	8	10	15	20	25	32	40	50		
1/4 ^B	3,430	4,240	4,240							
3/8	3,610	4,500	4,500	7,090						
1/2	4,470	5,600	5,600	7,580	10,100	12,800	14,700	17,000	44,000	
3/4	5,150	6,470	6,470	8,840	11,500	14,900	16,300	19,300	53,500	
1	6,480	8,170	8,170	12,600	16,000	21,100	24,100	28,500	68,000	
1 1/4	11,200	14,000		18,900	22,200	31,200	30,300	36,100	101,000	
1 1/2	14,700	18,400		24,500	28,100	40,600	38,500	46,400	113,000	
2	20,100	25,200		33,600	38,500	56,000	53,700	64,300	138,000	

(単位：円)

Aシリーズ(適用規格：ANSI B16.34 管接続部：フランジJIS B2210/ANSI B16.5)										
外観形状	静電防止機構付 									
型式	フルボア						レデューストボア			
ボディ/ボール	SCS13A/SUS304	SCS14A/SUS304	SCS13A/SUS304		SCS14A/SUS304		SCS16/SUS316L	SCS13A/SUS304	SCS14A/SUS304	
シート	PTFE			ハイパタイトPTFE						
管接続部	ねじ込			フランジ						
製品番号	10UT	10UTM	10UTBD (G-10UTBD)	10UTB (G-10UTB)	10UTBDM (G-10UTBDM)	10UTBM (G-10UTBM)	10UTBO	10UTR	10UTRM	
呼径	10 ^A	15	20	25	32	40	50	65	80	100
3/8 ^B	14,000	19,700								
1/2	14,900	20,600	25,600	25,600	35,900	35,900	45,100			
3/4	18,100	25,200	29,400	29,400	41,400	41,400	52,400			
1	23,600	32,700	41,200	41,200	57,700	57,700	73,200			
1 1/4	33,500	46,900	52,200	52,200	73,000	73,000	93,000			
1 1/2	44,900	62,500	55,900	55,900	78,300	78,300	99,500			
2	57,000	79,600	71,100	71,100	99,400	99,400	128,000	◎		◎
2 1/2	91,600	129,000	104,000	104,000	147,000	147,000	190,000	◎		◎
3	123,000	172,000	124,000	124,000	176,000	176,000	222,000	◎		◎
4			184,000	184,000	255,000	255,000	327,000	◎		◎
5			426,000	426,000	592,000	592,000	751,000	309,000		432,000
6			524,000	524,000	733,000	733,000	932,000	457,000		639,000
8			870,000	870,000	1,217,000	1,217,000	1,547,000	654,000		919,000
10			◎1,987,000	◎1,987,000	◎2,727,000	◎2,727,000	◎	1,018,000		1,425,000
12								◎2,121,000	◎	◎

注)10UTBD、10UTBDM は ASMEB 16.10 クラス 150 面間です。

◎印はギア式です。製品番号の先頭に「G」が付きます。

(単位：円)